



QUIETO

Kit pétales



MYO_FP-05/2023

Garantie
5 ANS



Since 2020

myO

AVANTAGES ESTHÉTIQUES

Ilôt unicolore de 3 formes géométriques indépendantes
3 tissus - Plus de 60 coloris
Facilement réglable en hauteur

AVANTAGES TECHNIQUES

Performance acoustique certifiée ($\alpha_w = 1$)
Réaction au feu : B-s2-d0 (Twist - Twist Melange)
Absence de rotation du panneau sur lui-même
Adaptation produit sur demande

QUIETO

Kit pétales


Facile à installer, le kit Pétales apporte un design léger et aérien dans les espaces tout en diminuant significativement la réverbération du son dans la pièce. Il se compose de 3 pétales (panneaux acoustiques) unicolores de dimensions différentes, sans cadre apparent.

| FIXATIONS | FINITIONS TISSUS | | | RÉACTION AU FEU |
|---------------------------|---------------------------------------|--|--------------------------------------|--|
| Suspension horizontale | TWIST Trevira CS 100% polyester | TWIST MÉLANGE Trevira CS 100% polyester | HUSH 80% polyester 20% viscose | B-s2-d0 en finitions Twist & Twist melange |
| Câbles (hauteur réglable) | 18 coloris | 17 coloris | 28 coloris | |

Dimensions & poids moyens

| KIT PÉTALES = 3 PANNEAUX ACOUSTIQUES | | POIDS MOYEN NET (KG) SANS EMBALLAGE |
|---|-------------|--|
| 1 | ±977*693 mm | 1,6 |
| 2 | ±749*525 mm | 0,8 |
| 3 | ±642*475 mm | 0,6 |
| Surface totale équivalente à ±1 m ² ≈ surface de 3 dalles de plafond standard | | 3 |

Epaisseur :
50 mm (±5 mm)



QUIETO

Kit pétales

myo-solutions.com

Acoustique

L'acoustique des produits destinés au plafond est généralement exprimée en α_w . Le coefficient d'absorption α_w (alpha w) permet de caractériser par une valeur unique la performance d'un produit. Il varie entre 0 (produit totalement réfléchissant) et 1 (produit totalement absorbant). Plus α_w est proche de 1, meilleure est son absorption.

| f (Hz) | α_s |
|--------|------------|
| 100 | 0,35 |
| 125 | 0,52 |
| 160 | 0,88 |
| 200 | 0,84 |
| 250 | 0,99 |
| 315 | 1,07 |
| 400 | 1,06 |
| 500 | 0,95 |
| 630 | 0,88 |
| 800 | 0,93 |
| 1000 | 1,03 |
| 1250 | 0,98 |
| 1600 | 1,09 |
| 2000 | 1,07 |
| 2500 | 1,08 |
| 3150 | 1,10 |
| 4000 | 1,11 |
| 5000 | 1,18 |

NF EN ISO 354



CSTB
le futur en construction

QUIETO

Kit pétales

myo-solutions.com

Kits fixation

Le système de suspension garantit une absence de rotation et un réglage facilité de la hauteur de chaque pétale.

Chaque pétale, équipé de 3 câbles, ne nécessite que 2 points de fixation au plafond.



SUSPENSION HORIZONTALE

Fixation par câbles dans le plafond.
longueur de câble fournie : 1,5 à 2 m

Faux-plafond (T24): KITFIHORT24PETL

La suspension d'objet sur T24 n'est autorisée qu'en cas de renforcement de l'ossature plafond (norme NF DTU 58.1)

Plâtre ou bois : KITFIHORPBETL

30 à 45 mn
(selon support)

Dalle béton : KITFIHORDALPETL





Montage

Pour permettre un montage soigné, les produits myO sont livrés avec : une notice de montage + une paire de gants en coton.

QUIETO

Petals kit



MYO_FP-05/2023

5-YEAR
Guarantee



Since 2020

myO

AESTHETIC BENEFITS

Island of 3 geometric unicouleur shapes
3 fabrics - More than 60 colors
Easily adjustable in height

TECHNICAL BENEFITS

Certified acoustic performance ($\alpha_w = 1$)
Fire-rated: B-s2-d0 (Twist - Twist Melange)
No rotation of the panel on itself
Product adaptation on demand

QUIETO

Petals kit

Easy to install, the QUIETO Petals kit brings a light and airy design to spaces while significantly reducing the reverberation of sound in the room. It is made up of acoustic panels cut from the same fabric color in 3 different sizes.

| FIXINGS | FABRIC FINISHES | | | FIRE-RATED |
|----------------------------------|---------------------|--------------------------------|---|---|
| Horizontal suspension | TWIST Trevira CS | TWIST MELANGE Trevira CS | HUSH 80% polyester 20% viscose | B-s2-d0 with Twist & Twist melange finishes |
| Cables (height adjustable) | 18 colors | 17 colors | 28 colors | |


Dimensions & Average weights

| PETALS KIT = 3 ACOUSTIC PANELS | | AVERAGE WEIGHTS (KG) Without packaging |
|--|-------------|---|
| 1 | ±977*693 mm | 1,6 |
| 2 | ±749*525 mm | 0,8 |
| 3 | ±642*475 mm | 0,6 |
| Making a surface equivalent to ±1 m ² ≈ surface of 3 standard ceiling panels | | 3 |

Product Adaptation

A different finish in a fabric other than those offered by myO is possible after validation of the technical and dimensional characteristics.

Thickness:
50 mm (±5 mm)



QUIETO

Petals kit


myo-solutions.com

Acoustic

Unit of measurement for ceiling product's acoustic is α_w .
The absorption coefficient α_w (alpha w) is used to characterise a product's performance through a unique value. It ranges between 0 (product totally reflective) and 1 (product totally absorbent).
The more α_w is closer to 1, the better the absorption.

| f (Hz) | α_s |
|---------------------------------------|------------|
| QUIETO CEILING PANEL 595x595x50 mm | |
| 100 | 0,35 |
| 125 | 0,52 |
| 160 | 0,88 |
| 200 | 0,84 |
| 250 | 0,99 |
| 315 | 1,07 |
| 400 | 1,06 |
| 500 | 0,95 |
| 630 | 0,88 |
| 800 | 0,93 |
| 1000 | 1,03 |
| 1250 | 0,98 |
| 1600 | 1,09 |
| 2000 | 1,07 |
| 2500 | 1,08 |
| 3150 | 1,10 |
| 4000 | 1,11 |
| 5000 | 1,18 |

NF EN ISO 354



QUIETO

Petals kit

myo-solutions.com

Fixing systems

The suspension system guarantees no rotation and easy adjustment of the height of each petal.

Fixed to the ceiling, each of the petals is equipped with 3 suspension points (to prevent rotations) for 2 fixing ceiling points.



HORIZONTAL SUSPENSION
Fixing with cables from the ceiling.
Provided cable length: 1,5 to 2m

False-ceiling (T24)*: KITFIHORT24PETL

Suspending objects on T24 is only allowed if the ceiling frame has been reinforced.

30 to 45 mn
(depending on the support)

Plaster or wood: KITFIHORPBPETL

Concrete slab: KITFIHORDALPETL



Assembly

To allow careful assembly, myO products are delivered with: assembly instructions + a pair of cotton gloves.